







Type	Dikte	Nr. Snijder	Parts p. Inch	Treksterkte	Doorlaatbaarheid
	<i>mm</i>	<i>2000 x 1000 mm</i>	<i>PPI</i>	<i>kPa</i>	<i>L / (m<sup>2</sup> x s)</i>
<b>PPI (PA ; PB ; PC)</b> 	5 mm	N20001000 <b>PA</b>	8 - 13	100	7500
	10 mm	N20001000 <b>PB</b>	8 - 13	100	7500
	20 mm	N20001000 <b>PC</b>	8 - 13	100	7500
<b>PPI (PE ; PF ; PG)</b> 	5 mm	N20001000 <b>PE</b>	16 - 23	120	5300
	10 mm	N20001000 <b>PF</b>	16 - 23	120	5300
	20 mm	N20001000 <b>PG</b>	16 - 23	120	5300
<b>PPI (PI ; PJ ; PK)</b> 	5 mm	N20001000 <b>PI</b>	27 - 34	150	3850
	10 mm	N20001000 <b>PJ</b>	27 - 34	150	3850
	20 mm	N20001000 <b>PK</b>	27 - 34	150	3850
<b>PPI (PM ; PN ; PO)</b> 	5 mm	N20001000 <b>PM</b>	41 - 49	180	2850
	10 mm	N20001000 <b>PN</b>	41 - 49	180	2850
	20 mm	N20001000 <b>PO</b>	41 - 49	180	2850
<b>PPI (PQ ; PR ; PS)</b> 	5 mm	N20001000 <b>PQ</b>	57 - 70	200	1850
	10 mm	N20001000 <b>PR</b>	57 - 70	200	1850
	20 mm	N20001000 <b>PS</b>	57 - 70	200	1850
<b>PPI (PU ; PV ; PW)</b> 	5 mm	N20001000 <b>PU</b>	75 - 90	250	1217
	10 mm	N20001000 <b>PV</b>	75 - 90	250	1217
	20 mm	N20001000 <b>PW</b>	75 - 90	250	1217

Temperatuur range: -40 tot +100 Celsius